

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** High Density (HDF), Medium Density (MDF) & Light Density (LDF) Fiberboard

### 1.2. Intended Use of the Product

Not available

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

Plum Creek Timber Company

P.O. Box 1990

Columbia Falls, MT 59912

T 406-892-6200

[www.plumcreek.com](http://www.plumcreek.com)

#### Manufacturer

Plum Creek MDF, Inc

265 Meadow Lake Blvd.

Columbia Falls, MT 59912

### 1.4. Emergency Telephone Number

**Emergency Number** : 406-892-6200

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### Classification (GHS-US)

Comb. Dust

Carc. 1A H350

Repr. 2 H361

STOT RE 1 H372

Aquatic Acute 3 H402

Full text of H-phrases: see section 16

### 2.2. Label Elements

#### GHS-US Labeling

**Hazard Pictograms (GHS-US)** :



**Signal Word (GHS-US)** :

Danger

**Hazard Statements (GHS-US)** :

May form combustible dust concentrations in air.

H350 - May cause cancer.

H361 - Suspected of damaging fertility or the unborn child.

H372 - Causes damage to organs through prolonged or repeated exposure.

H402 - Harmful to aquatic life.

**Precautionary Statements (GHS-US)** :

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P314 - Get medical advice/attention if you feel unwell.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

# High Density (HDF), Medium Density (MDF) & Light Density (LDF) Fiberboard

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### 2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US) No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Not applicable

### 3.2. Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Wood dust, soft woods	(CAS No) RR-00514-1	88 - 92	Comb. Dust Carc. 1A, H350 STOT RE 1, H372
Slack wax, petroleum	(CAS No) 64742-61-6	< 1	Carc. 1B, H350 Repr. 2, H361 STOT RE 1, H372
Ammonia	(CAS No) 7664-41-7	< 1	Flam. Gas 2, H221 Liquefied gas, H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for several minutes. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persists. Remove contact lenses, if present and easy to do. Continue rinsing.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

**Inhalation:** May cause cancer by inhalation.

**Skin Contact:** Prolonged contact with large amounts of dust may cause mechanical irritation.

**Eye Contact:** Eye contact with large amounts of dust may cause mechanical irritation.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Causes damage to organs through prolonged or repeated exposure. May cause cancer. May damage fertility. May damage the unborn child.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Alcohol-resistant foam. Dry powder. Carbon dioxide. Water spray. Sand.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream.

# High Density (HDF), Medium Density (MDF) & Light Density (LDF) Fiberboard

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Combustible Dust. Dust explosion hazard in air. Supports combustion. High temperatures. Under conditions of fire this material may produce: Carbon dioxide. Carbon monoxide.

**Explosion Hazard:** Avoid dust clouds in combination with static electricity. Dust clouds can be explosive.

**Reactivity:** Stable at ambient temperature and under normal conditions of use.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>).

**Other Information:** Refer to Section 9 for flammability properties.

### Reference to Other Sections

Refer to section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid generating dust. Handle in accordance with good industrial hygiene and safety practice. Good housekeeping is needed during storage, transfer, handling, and use of this material to avoid excessive dust accumulation. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Eliminate ignition sources.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Material for Containment and Cleaning Up

**Methods for Cleaning Up:** Collect spillage. Avoid generation of dust during clean-up of spills. Vacuum must be fitted with HEPA filter to prevent release of particulates during clean-up. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Keep only in the original container in a cool, well ventilated place away from: Direct sunlight, Heat sources. Keep container closed when not in use. Protect from moisture.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

### 7.3. Specific End Use(s) Not available

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Wood dust, soft woods (RR-00514-1)		
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (total)

# High Density (HDF), Medium Density (MDF) & Light Density (LDF) Fiberboard

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Nunavut	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Québec	VEMP (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (except red cedar, containing no Asbestos and <1% Crystalline silica-total dust)
Yukon	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (non-allergenic) 5 mg/m <sup>3</sup> (allergenic, including cedar, mahogany, teak)
Yukon	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (non-allergenic) 2.5 mg/m <sup>3</sup> (allergenic, including cedar, mahogany, teak)
<b>Ammonia (7664-41-7)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	18 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	25 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	27 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	35 ppm
USA ACGIH	ACGIH TWA (ppm)	25 ppm
USA ACGIH	ACGIH STEL (ppm)	35 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	35 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	18 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	27 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	35 ppm
USA IDLH	US IDLH (ppm)	300 ppm
Alberta	OEL STEL (mg/m <sup>3</sup> )	24 mg/m <sup>3</sup>
Alberta	OEL STEL (ppm)	35 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	17 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	25 ppm
British Columbia	OEL STEL (ppm)	35 ppm
British Columbia	OEL TWA (ppm)	25 ppm
Manitoba	OEL STEL (ppm)	35 ppm
Manitoba	OEL TWA (ppm)	25 ppm
New Brunswick	OEL STEL (mg/m <sup>3</sup> )	24 mg/m <sup>3</sup>
New Brunswick	OEL STEL (ppm)	35 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	17 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	25 ppm
Newfoundland & Labrador	OEL STEL (ppm)	35 ppm
Newfoundland & Labrador	OEL TWA (ppm)	25 ppm
Nova Scotia	OEL STEL (ppm)	35 ppm
Nova Scotia	OEL TWA (ppm)	25 ppm
Nunavut	OEL STEL (mg/m <sup>3</sup> )	24 mg/m <sup>3</sup>
Nunavut	OEL STEL (ppm)	35 ppm
Nunavut	OEL TWA (mg/m <sup>3</sup> )	17 mg/m <sup>3</sup>
Nunavut	OEL TWA (ppm)	25 ppm
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	24 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (ppm)	35 ppm
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	17 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (ppm)	25 ppm
Ontario	OEL STEL (ppm)	35 ppm

# High Density (HDF), Medium Density (MDF) & Light Density (LDF) Fiberboard

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Ontario	OEL TWA (ppm)	25 ppm
Prince Edward Island	OEL STEL (ppm)	35 ppm
Prince Edward Island	OEL TWA (ppm)	25 ppm
Québec	VECD (mg/m <sup>3</sup> )	24 mg/m <sup>3</sup>
Québec	VECD (ppm)	35 ppm
Québec	VEMP (mg/m <sup>3</sup> )	17 mg/m <sup>3</sup>
Québec	VEMP (ppm)	25 ppm
Saskatchewan	OEL STEL (ppm)	35 ppm
Saskatchewan	OEL TWA (ppm)	25 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	30 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	40 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	18 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	25 ppm

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Provide adequate ventilation to minimize dust concentrations. Ensure all national/local regulations are observed. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

**Personal Protective Equipment:** Dust formation: dust mask. Gloves. Protective goggles. Dustproof clothing.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** Approved dust mask is required for some finishing operations such as sawing or sanding where dust is created.

**Environmental Exposure Controls:** Do not allow the product to be released into the environment.

**Consumer Exposure Controls:** Do not eat, drink or smoke during use

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Not available
Odor	: Not available
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available

# High Density (HDF), Medium Density (MDF) & Light Density (LDF) Fiberboard

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Not available
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Static discharge could act as an ignition source.

### SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Stable at ambient temperature and under normal conditions of use.
- 10.2. **Chemical Stability:** Stable under normal conditions.
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Protect from moisture. Use good housekeeping practices during storage, transfer, and handling, to avoid excessive dust accumulation.
- 10.5. **Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.
- 10.6. **Hazardous Decomposition Products:** Under conditions of fire this material may produce: Carbon oxides (CO, CO<sub>2</sub>).

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: May cause cancer.

**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs through prolonged or repeated exposure.

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** Not classified

Aspiration Hazard: Not classified

**Symptoms/Injuries After Inhalation:** May cause cancer by inhalation.

**Symptoms/Injuries After Skin Contact:** Prolonged contact with large amounts of dust may cause mechanical irritation.

**Symptoms/Injuries After Eye Contact:** Eye contact with large amounts of dust may cause mechanical irritation.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Causes damage to organs through prolonged or repeated exposure. May cause cancer. May damage fertility. May damage the unborn child.

#### 11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Ammonia (7664-41-7)	
LC50 Inhalation Rat	5.1 mg/l (Exposure time: 1 h)
LC50 Inhalation Rat	2000 ppm/4h (Exposure time: 4 h)
ATE US (vapors)	5.10 mg/l/4h
ATE US (dust, mist)	5.10 mg/l/4h
Wood dust, soft woods (RR-00514-1)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

# High Density (HDF), Medium Density (MDF) & Light Density (LDF) Fiberboard

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1. Toxicity

**Ecology - General:** Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

<b>Ammonia (7664-41-7)</b>	
LC50 Fish 1	0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio)
EC50 Daphnia 1	25.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	0.26 - 4.6 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

#### 12.2. Persistence and Degradability

<b>High Density (HDF), Medium Density (MDF) &amp; Light Density (LDF) Fiberboard</b>	
Persistence and Degradability	May cause long-term adverse effects in the environment.

#### 12.3. Bioaccumulative Potential

<b>High Density (HDF), Medium Density (MDF) &amp; Light Density (LDF) Fiberboard</b>	
Bioaccumulative Potential	Not established.
<b>Ammonia (7664-41-7)</b>	
Log Pow	-1.14 (at 25 °C)

12.4. Mobility in Soil Not available

#### 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

### SECTION 14: TRANSPORT INFORMATION

- 14.1. In Accordance with DOT Not regulated for transport
- 14.2. In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport
- 14.4. In Accordance with TDG Not regulated for transport

### SECTION 15: REGULATORY INFORMATION

#### 15.1. US Federal Regulations

<b>High Density (HDF), Medium Density (MDF) &amp; Light Density (LDF) Fiberboard</b>	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
<b>Slack wax, petroleum (64742-61-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Ammonia (7664-41-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard
SARA Section 313 - Emission Reporting	1.0 % (includes anhydrous Ammonia and aqueous Ammonia from water dissociable Ammonium salts and other sources, 10% of total aqueous Ammonia is reportable under this listing)

#### 15.2. US State Regulations

# High Density (HDF), Medium Density (MDF) & Light Density (LDF) Fiberboard

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Wood dust, soft woods (RR-00514-1)</b>	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Formaldehyde (50-00-0)</b>	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Wood dust, soft woods (RR-00514-1)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List	
<b>Ammonia (7664-41-7)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	

### 15.3. Canadian Regulations

<b>High Density (HDF), Medium Density (MDF) &amp; Light Density (LDF) Fiberboard</b>	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
	
<b>Wood dust, soft woods (RR-00514-1)</b>	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Slack wax, petroleum (64742-61-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Ammonia (7664-41-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 06/16/2015  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B

# High Density (HDF), Medium Density (MDF) & Light Density (LDF) Fiberboard

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Gas 2	Flammable gases Category 2
Liquefied gas	Gases under pressure Liquefied gas
Repr. 2	Reproductive toxicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H221	Flammable gas
Comb. Dust	May form combustible dust concentrations in air
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects

### Party Responsible for the Preparation of This Document

Plum Creek Timber Company  
Phone Number: 406-892-6200

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS 2